

USSN 09/553,108  
Atty. Docket No. GJH-0017

-4-

**REMARKS**

Pages 26-31 have been replaced with the attached pages 26-31. The changes on pages 26-31 are to correct the mislabeling of Examples and correct references to these Examples in the specification. More specifically, the number 5 is used in the Examples twice, once for Examples 1-5 in Table 1 and once for Example 5 in Table 4. Therefore, the second reference to Example 5 was changed to Example 7 in Table 4 and the supporting paragraphs for Table 4. In changing the second reference to "Example 5" to Example 7, the reference to Example 7 on pages 29-31 was changed to refer to this Example as Example 8. No new matter has been added.

Claim 4 has been cancelled as the majority of its contents have been incorporated into amended Claim 1.

Applicants have amended Claims 1, 22, 30, 31, and 32 to delete the limitation that the T95 point of the distillate fuel compositions and distillate of Claim 32 is greater than about 335.

Applicants have also amended Claims 1, 31, and 32 to include the limitation that the distillate fuel has a total aromatics content of about 20 to 35 wt.%. Supports for this amendment can be found in original Claim 4 as filed, and page 14, second paragraph of the instant specification.

Applicants request that the Examiner enter all amended claims and pages in order to place this application in condition for allowance or in better form for appeal.

Applicants submit herewith a Petition to Revive and the required fee for the unintentional abandonment of the instant application.

USSN 09/553,108  
Atty. Docket No. GJH-0017

-5-

Applicants also submit herewith a Change of Correspondence Address form and a Request for Continued Examination.

**OBJECTION UNDER 35 U.S.C. 132(b)**

The amendment filed January 3, 2002 has been objected to under 35 U.S.C. 132(b) because it introduces new matter.

**EXAMINER'S POSITION**

The Examiner takes the position that there is no support for the limitation of a T95 point "greater than about 335°C".

**APPLICANTS' POSITION**

Applicants have removed this limitation from Claims 1, 22, 30, 31, and 32. The Examiner is requested to withdraw this objection.

**REJECTION UNDER 35 U.S.C. 112, FIRST PARAGRAPH**

Claims 1-32 have been rejected under 35 U.S.C. 112, first paragraph as containing subject matter which was not described in the specification in such a way as to reasonably convey to one skilled in the art that the inventor(s), at the time the application was filed, had possession of the claimed.

**EXAMINER'S POSITION**

There is no support for the claimed "greater than about 335°C" limitation.

**APPLICANTS' POSITION**

Applicants have removed this limitation from Claims 1, 22, 30, 31, and 32. The Examiner is requested to reconsider and withdraw this rejection.

USSN 09/553,108  
Atty. Docket No. GJH-0017

-6-

**REJECTION UNDER 35 U.S.C. 103(a)**

Claims 1-3, 6-9, 14-21, 34 and 35 are rejected under 35 U.S.C. 103(a) as being obvious over United States Patent Number 6,150,575 Angevine et al. ("Angevine").

**EXAMINER'S POSITION**

It is the Examiner's position that Angevine teach diesel fuel having good ignition qualities, good combustion emission performance, and good low temperature characteristics. Such a fuel is characterized as having a cetane number of at least 45, a total aromatics content of 10 to 15 wt.%, a polynuclear aromatics content of less than 11 wt.%, and a sulfur content of not more than 50 ppm. The Examiner points out that Table 3 of Angevine discloses preferred compositional parameters for the fuel and that Table 4, Example 1 teaches a diesel fuel having 14 wt.% total aromatics, 0.6 wt.% polynuclear aromatics, 13 ppm sulfur, an initial boiling point of 183°C, T10 point of 225°C, and a final boiling of 360°C.

The Examiner states that the instant claims are directed to compositions comprising "about 20 wt.% aromatics," i.e. the claims include compositions wherein the total aromatics are less than 20 wt.%. Accordingly, the Examiner takes the positions that it should have been obvious to one having ordinary skill in the art at the time the invention was made to increase the amount of aromatics in the diesel fuel taught by Angevine to a maximum amount of "about 20 wt.%" based on the expectation that such a diesel would have similar properties. The Examiner also takes the position that the claimed T95 point is obvious in light of Example 2 of Angevine.

**APPLICANTS' POSITION**

Applicants respectfully disagree with the Examiner as it is their position that Angevine does not render obvious the instantly claimed invention. The instantly claimed invention, as amended, requires that the distillate fuel composition have a Total

USSN 09/553,108  
Atty. Docket No. GJH-0017

-7-

Aromatics concentration of from about 20-35 wt.%, as described in Claims 1, 22, 31, and 32, and from about 25-35 wt.% in Claim 30.

There is no teaching in Angevine to suggest that the amount of Total Aromatics disclosed and claimed therein should be increased to the presently claimed range. Angevine discloses that the "board value" of Total Aromatics is less than 10, and that the "preferred value" is between 10-15, see Table 3 of Angevine. Table 3 also discloses an optimum value but gives no range. However, col. 4, states that "the observance of certain narrower ranges within the ranges described above may however lead to an enhancement of overall performance, an improvement in product economics or both. Suitable preferred ranges are set out in Table 3, using the same tests as listed in Table 2 above.", see Angevine col.4, lines 53-58. Table 2 of Angevine discloses a Total Aromatics content of between 10-15 wt.%. Further, all of the Examples contained within the Angevine patent are below 15 wt.% Total Aromatics.

Therefore, Angevine does not teach nor suggest that one should have a Total Aromatics content within the presently claimed range of 20-35 wt.%. Instead, Angevine teaches that narrower ranges within the 10-15 wt.% Total Aromatics range would be beneficial. There is no disclosure that one should increase the range of Total Aromatics beyond 15 wt.%.

The Examiner is requested to reconsider and withdraw this rejection.


USSN 09/553,108  
Atty. Docket N . GJH-0017

-8-

Based on the preceding arguments and amendments, the Examiner is requested to reconsider and withdraw all rejections and objections, and pass this application to allowance. The Examiner is encouraged to contact applicants' attorney should the Examiner wish to discuss this application further.

Respectfully submitted:

Date: 1-22-03

  
\_\_\_\_\_  
Jeremy J. Kliebert, Registration No. 48,227  
Attorney for Applicants  
Telephone: (225) 977-1592  
Facsimile: (225) 977-1025

*Correspondence Address:*  
ExxonMobil Research and Engineering Company  
P. O. Box 900  
Annandale, New Jersey 08801-0900

USSN 09/553,108  
Atty. Docket No. GJH-0017

-9-

**MARKED-UP CLAIMS ACCOMPANYING RESPONSE TO FINAL OFFICE ACTION FOR  
USSN 09/553,108:**

1. (twice amended) A distillate fuel composition boiling in the range of about 190°C to 400°C with a T10 point greater than 205°C, [a T95 point of greater than about 335], and having a sulfur level of less than about 100 wppm, a total aromatics content of about ]15] 20 to about 35 wt.%, a polynuclear aromatics content of less than about 3 wt.%, and wherein the ratio of total aromatics to polynuclear aromatics is greater than about 11.
22. (twice amended) A distillate fuel composition boiling in the range of about 190°C to 400°C with a T10 point greater than 205°C, [a T95 point of greater than about 335], and having a sulfur level of less than about 50 wppm, a total aromatics content of 20 to about 35 wt.%, a polynuclear aromatics content of less than about 2 wt.%, and wherein the ratio of total aromatics to polynuclear aromatics is greater than about 13.
30. (twice amended) An automotive distillate fuel composition boiling in the range of about 190°C to 400°C with a T10 point greater than 205°C, [a T95 point of greater than about 335°C], and having a sulfur level of less than about 10 wppm, a total aromatics content of about 25 to 35 wt.%, a polynuclear aromatics content of less than about 1 wt.%, wherein the ratio of total aromatics to polynuclear aromatics ranges from about 15 to about 25.
31. (twice amended) A method for abating particulate and Nox emissions in a compression ignition engine comprising providing to the engine a distillate fuel composition boiling in the range of about 190°C to 400°C with a T10 point greater than 205°C, [a T95 point of greater than about 335], and having a sulfur level of less than about 100 wppm, a total aromatics content of about [15] 20 to

USSN 09/553,108  
Atty. Docket No. GJH-0017

-10-

35 wt.%, a polynuclear aromatics content of less than about 3 wt.%, and wherein the ratio of total aromatics to polynuclear aromatics is greater than about 11.

32. (twice amended) A fuel composition comprising a distillate boiling in the range of about 190°C to 400°C with a T10 point greater than 205°C, [a T95 point of greater than about 335°C], and having a sulfur level of less than about 100 wppm, a total aromatics content of about 20 [15] to 35 wt.%, a polynuclear aromatics content of less than about 3 wt.%, and wherein the ratio of total aromatics to polynuclear aromatics is greater than about 11, to which is added at least one of (i) one or more lubricity aid, (ii) one or more viscosity modifier, (iii) one or more antioxidant, (iv) one or more cetane improver, (v) one or more dispersant, (vi) one or more cold flow improver, (vii) one or more metals deactivator, (viii) one or more corrosion inhibitor, (ix) one or more detergent, and (x) one or more distillate or upgraded distillate.